

OUTPUT CONTROL DEVICE FOR FUEL CELL POWER GENERATING SYSTEM


Publication number: JP4058463
Publication date: 1992-02-25
Inventor: KOMATSU TADASHI
Applicant: FUJI ELECTRIC CO LTD
Classification:
- international: H01M8/04; H01M8/04; (IPC1-7): H01M8/04
- european:
Application number: JP19900166291 19900625
Priority number(s): JP19900166291 19900625

BEST AVAILABLE COPY

Report a data error here

Abstract of JP4058463

PURPOSE: To hold the proper utilization factor of reaction gas and stabilize the power generation of a fuel cell without impairing load responsiveness by collating the product of the current and voltage on a characteristic curve and a power command value to determine the target current value, and controlling the feed quantities of fuel gas and reaction air based on the target current value. **CONSTITUTION:** The feed quantity of reaction gas to a fuel cell I is controlled by a target current estimation section 11 which receives the detected signals of detectors 14, 15 of the output current I_f and output voltage V_f of the fuel cell I and outputs the target current estimated value I_{fb} corresponding to a power command 20 and a reaction gas quantity calculation section 12 which receives the command value of the target current I_{fb} , calculates the reaction gas quantity corresponding to it, and outputs command signals 14F, 15A to an auxiliary machine controller. A response correcting circuit 13 delays the rising time and trailing time of the square-wave power command 20 to feed it to a controller 8, and the response speed of a power converter 7 is delayed to the response speed of a fuel reformer to control the output.



Data supplied from the esp@cenet database - Worldwide